ASSA ABLOY Desmo⁺ 8950

Cam Lock





Performance

ASSA ABLOY Desmo $^+$ is a high security cylinder design based on direct driven pins.

ASSA ABLOY Desmo⁺ 8950 is an 8-pin camlock to be used on doors with 18/22 hole and up to 16 mm thickness.

The ASSA ABLOY Desmo⁺ 8-pin design allows master keying and the technology creates a high number of differs.

Cylinders are made of nickel plated brass and the keys of nickel silver. Drill protection and double key entry is available on request.

ASSA ABLOY standard catches can be used.

Function

The key turns 90° and can only be removed when the catch is in the locked position. Double key entry is available on request.

Right hand turning as standard and left hand available on request.







ASSA ABLOY Desmo⁺ 8950


Cam Lock

Dimension (mm)





Hole preparation



Included in part no: 492362

| Part | Part no | Material | Finish | Notes |
|----------------|---------|----------|---------------|---|
| Large nut | 490610 | Steel | Zinc plated | Catch Preparation: |
| Small nut | 490583 | Steel | Zinc plated | • Locking up or down = horizontal hole ir |
| Stop washer | 492291 | Brass | Nickel plated | • Locking right or left = vertical hole in ca |
| Locking washer | 490246 | Steel | Zinc plated | Cylinder house: Nickel plated brass |
| | | | | Cylinder: Brass |

Keys

Keys together with lock 492366 Extra keys 492373

ASSA ABLOY Opening Solutions Sweden P.O. Box 371 SE-631 05 Eskilstuna Sweden Phone +46 (0)16 17 70 00 Fax +46 (0)16 17 70 49

Customer support: Phone intl. +46 (0)16 17 71 00 Phone nat. 0771-640 640 Fax +46 (0)16 17 73 72 e-mail: helpdesk.se.openingsolutions@assaabloy.com www.assaabloyopeningsolutions.se

- in catch
- atch

Accessories see data sheet "Accessories" Catches see data sheet "Catches" Spare parts see data sheet "Spare Parts"

